



ICY - UNIT COOLER

TECHNICAL DATA



Model	Capacity		Air throw	Air flow	Sound Level	Connection	Fan	Defrost		weight	Dimension		
	Te ±0℃	Te -18℃						coil	tray		L	W	H
	DT1 8K	DT1 7K											
	kW	kW	m	m³/h	dB(A)	φmm	Qy x mm	W	W	kg	m		
													
DL16	3.2	2.5	10	3,126	66	12 / 22	2 x 300	4x0.32	2x0.32	35	1020	330	460
DL20	4.1	3.2	10	3,126	66	12 / 22	2 x 300	4x0.32	2x0.32	38	1110	330	460
DL30	6.1	4.7	12	4,580	71	16 / 28	2 x 350	4x0.50	2x0.50	50	1470	330	460
DL40	8.0	6.2	12	4,580	71	16 / 28	2 x 350	6x0.49	2x0.49	57	1400	380	570
DL60	11.2	8.7	13	6,800	75	16 / 35	2 x 400	6x0.51	2x0.51	68	1450	380	670
DL80	16.2	12.6	15	13,140	81	22 / 50	2 x 500	6x0.61	2x0.61	96	1700	470	670
DL105	21.5	16.7	15	13,140	81	22 / 50	2 x 500	6x0.81	2x0.81	114	2200	470	670
DL135	27.6	21.4	17	19,710	83	22 / 50	3 x 500	8x0.83	2x0.83	143	2250	570	670
DL160	32.8	25.4	17	19,710	83	22 / 50	3 x 500	8x1.00	2x1.00	179	2750	570	670
DL185	37.6	29.1	18	26,280	85	22 / 50	4 x 500	8x1.10	2x1.10	214	3000	570	670
DL210	42.7	33.1	18	26,280	85	22 / 50	4 x 500	10x1.10	2x1.10	225	2900	570	670
DL260	52.9	41.0	20	26,160	84	22 / 50	3 x 550	14x1.20	2x1.20	261	3200	620	770
DL330	67.6	52.4	20	34,880	86	22 / 50	4 x 550	16x1.10	2x1.20	320	3000	720	770
DL400	82.0	63.6	20	43,280	87	22 / 54	4 x 600	16x1.30	2x1.30	360	3400	720	770

													
DD12	2.8	2.2	10	3,126	66	12 / 22	2 x 300	4x0.32	2x0.32	34	1020	330	460
DD15	3.6	2.8	10	3,126	66	12 / 22	2 x 300	4x0.32	2x0.32	37	1110	330	460
DD22	4.8	3.7	12	4,580	71	16 / 28	2 x 350	4x0.50	2x0.50	49	1470	330	460
DD30	7.4	5.7	12	4,580	71	16 / 28	2 x 350	6x0.49	2x0.49	56	1400	380	570
DD40	9.7	7.5	13	6,800	75	16 / 35	2 x 400	6x0.51	2x0.51	67	1450	380	670
DD60	14.7	11.4	15	13,140	81	22 / 50	2 x 500	6x0.61	2x0.61	95	1700	470	670
DD80	19.6	15.2	15	13,140	81	22 / 50	2 x 500	6x0.81	2x0.81	113	2200	470	670
DD100	24.1	18.7	17	19,710	83	22 / 50	3 x 500	8x0.83	2x0.83	142	2250	570	670
DD120	28.9	22.4	17	19,710	83	22 / 50	3 x 500	8x1.00	2x1.00	178	2750	570	670
DD140	33.8	26.2	18	26,280	85	22 / 50	4 x 500	8x1.10	2x1.10	213	3000	570	670
DD160	38.7	30.0	18	26,280	85	22 / 50	4 x 500	10x1.10	2x1.10	224	2900	570	670
DD200	48.2	37.4	20	26,160	84	22 / 50	3 x 550	14x1.20	2x1.20	260	3200	620	770
DD250	60.4	46.8	20	34,880	86	22 / 50	4 x 550	16x1.10	2x1.20	317	3000	720	770
DD300	72.5	56.2	20	43,280	87	22 / 54	4 x 600	16x1.30	2x1.30	359	3400	720	770

													
DJ8	2.4	1.9	10	3,126	66	12 / 22	2 x 300	4x0.32	2x0.32	34	1020	330	460
DJ10	3.1	2.4	10	3,126	66	12 / 22	2 x 300	4x0.32	2x0.32	37	1110	330	460
DJ15	4.1	3.1	12	4,580	71	16 / 28	2 x 350	4x0.50	2x0.50	49	1470	330	460
DJ20	6.3	4.8	12	4,580	71	16 / 28	2 x 350	6x0.49	2x0.49	56	1400	380	570
DJ30	8.2	6.4	13	6,800	75	16 / 35	2 x 400	6x0.51	2x0.51	67	1450	380	670
DJ40	12.5	9.7	15	13,140	81	22 / 50	2 x 500	6x0.61	2x0.61	95	1700	470	670
DJ55	16.7	12.9	15	13,140	81	22 / 50	2 x 500	6x0.81	2x0.81	113	2200	470	670
DJ70	20.5	15.9	17	19,710	83	22 / 50	3 x 500	8x0.83	2x0.83	142	2250	570	670
DJ85	24.6	19.0	17	19,710	83	22 / 50	3 x 500	8x1.00	2x1.00	178	2750	570	670
DJ100	28.7	22.3	18	26,280	85	22 / 50	4 x 500	8x1.10	2x1.10	213	3000	570	670
DJ115	32.9	25.5	18	26,280	85	22 / 50	4 x 500	10x1.10	2x1.10	224	2900	570	670
DJ140	41.0	31.8	20	26,160	84	22 / 50	3 x 550	14x1.20	2x1.20	260	3200	620	770
DJ170	51.3	39.8	20	34,880	86	22 / 50	4 x 550	16x1.10	2x1.20	317	3000	720	770
DJ210	61.6	47.8	20	43,280	87	22 / 54	4 x 600	16x1.30	2x1.30	359	3400	720	770